



Pall Filter (BeiJing) Co., Ltd
Tel: 021-62371988 Fax: 021-62372088

Dragon Aromatics (Zhangzhou) Co; Ltd
询价号: 413061-1000-EN30-TER-0002

2.1.4 41-F-201A/B; 43-F-201A/B Feed Filters

Specification Sheet

Operating Conditions

Type of fluid to be Filtered	Xylenes
Operating Pressure/Temperature	2.37Mpa(g) @ 175 °C
Flow	710.7m3/h
Density	867.4kg/m3@15°C, 727.3kg/m3@PT
Viscosity	0.20cp@PT
Rating	10 um
Required Clean DP	by vendor
Required Dirty DP	0.15Mpa

Housing

Housing Part Number	R48EC-4G193CH25P4-CC9406
Number of Housing Required	4
Manufacture	Pall China
Manufacture Code	GB150-98
Housing Material of Construction	Q345R
Closure Seal	304/Graphite
Design Pressure/ Temperature	3.49Mpa @ 195°C
Dimensions	Φ600×H3438 (mm)
Volume capacity	0.79m3
Net Weight	1250kg
Inlet/Outlet	12" ASME 300# WNRF
Designed Clean DP	0.02MPa
Designed Dirty DP	0.28Mpa
Design Flow	800m3/h

Element (for start-up)

Cartridge P/N	G100AW40S-1PK
Material	Heat Purified Glass Fiber
Manufacture	Pall USA
Number of Elements Required	192 pcs (48pcs per filter)
Filtration Area	0.205m2/pcs
Total Area per filter	9.84m2
Cartridge Description	OD.2 1/2"×H 40"
Removal rating	100um (99%)



Pall Filter (BeiJing) Co., Ltd
Tel: 021-62371988 Fax: 021-62372088

Dragon Aromatics (Zhangzhou) Co; Ltd
询价号: 413061-1000-EN30-TER-0002

2.1.5 41-F-202A/B; 43-F-202A/B Desorbent Filters Specification Sheet

Operating Conditions

Type of fluid to be Filtered	PDEB+ C10 aromatic
Operating Pressure/Temperature	2.37Mpa(g) @ 175 °C
Flow	972.5m3/h
Density	865.6kg/m3@15°C, 743.3kg/m3@PT
Viscosity	0.25cp@PT
Rating	10 um
Required Dirty DP	0.15Mpa

Housing

Housing Part Number	R72EC-4G225CH25P4-CC9407
Number of Housing Required	4
Manufacture	Pall China
Manufacture Code	GB150-98
Housing Material of Construction	Q345R
Closure Seal	304/Graphite
Design Pressure/ Temperature	3.73Mpa @ 195°C
Dimensions	Φ700×H3477 (mm)
Volume capacity	1.1m3
Net Weight	1650 kg
Inlet/Outlet	14" ASME 300# WNRF
Designed Clean DP	0.02MPa
Designed Dirty DP	0.28MPa
Designed Flow	1100m3/h

Element (for start-up)

Cartridge P/N	G100AW40S-1PK
Material	Heat Purified Glass Fiber
Manufacture	Pall USA
Number of Elements Required	288pcs (72pcs per filter)
Cartridge Description	OD.2 1/2"×H 40"
Filtration Area	0.205m2/pcs
Total Area per filter	14.8m2
Removal Rating	100um (99%)

2



Pall Filter (BeiJing) Co., Ltd
Tel: 021-62371988 Fax: 021-62372088

Dragon Aromatics (Zhangzhou) Co; Ltd
询价号: 413061-1000-EN30-TER-0002

2.1.6 41-F-203A/B; 43-F-203A/B Backwash Filters

Specification Sheet

Operating Conditions

Type of fluid to be Filtered	Paraxylene
Operating Pressure/Temperature	2.37Mpa(g) @ 155 °C
Flow	72.8m ³ /h
Density	746.1kg/m ³
Viscosity	0.21cp@PT
Rating	10 um
Required Dirty DP	0.15MPa

Housing

Housing Part Number	R07EC-4G65H25-CC9408
Number of Housing Required	4
Manufacture	Pall China
Manufacture Code	GB150-98
Housing Material of Construction	Q345R
Closure Seal	304/Graphite
Design Pressure/ Temperature	3.81Mpa @ 184 °C
Dimensions	Φ325×H2070(mm)
Volume capacity	0.11m ³
Inlet/Outlet	4" ASME 300# WNRF
Designed Clean DP	0.02MPa
Designed Dirty DP	0.28Mpa
Design Flow rate	80m ³ /h

Element (for start-up)

Cartridge P/N	G100AW40S-1PK
Material	Heat Purified Glass Fiber
Manufacture	Pall USA
Number of Elements Required	28pcs (7pcs per filter)
Filtration Area	0.205m ² /pcs
Total Area per filter	1.435m ²
Cartridge Description	OD.2 1/2"×H 40"
Removal Rating	100um(99%)